

DELPHION

No active trail

Select ER

Stop tracking

RESEARCH

PRODUCTS

INSIDE DELPHION

Log Out Work Files Saved Searches

My Account

Search: Quick/Number Boolean Advanced Derwent

Help

The Delphion Integrated View

Get Now: ☒ PDF | File History | Other choices

Tools: Add to Work File: Create new Work File

Add

View: INPADOC | Jump to: Top

Go to: Derwent

☐ Email this to a friend

Title: JP2000067853A2: NEGATIVE ELECTRODE FOR LITHIUM SECONDARY BATTERY

Derwent Title: Negative electrode for lithium secondary battery having non-aqueous electrolyte - consists of a molded part of mixture containing lithium-containing composite nitride, carbon material, and binder [Derwent Record]

Country: JP Japan

Kind: A2 Document Laid open to Public inspection

Inventor: HASEGAWA MASAKI;
YAMAURA JUNICHI;
FUJINO MAKOTO;
TSUTSUMI SHUJI;
KONDO SHIGEO;
MASASHIRO TAKAHISA;
SAKURAI YOJI;

Assignee: MATSUSHITA BATTERY INDUSTRIAL CO LTD
NIPPON TELEGR & TELEPH CORP <NTT>
News, Profiles, Stocks and More about this company

Published / Filed: 2000-03-03 / 1998-08-18


Application Number: JP1998000232027

IPC Code: Advanced: H01M 4/02; H01M 4/58; H01M 10/40;
Core: H01M 10/36; more...
IPC-7: H01M 4/02; H01M 4/58; H01M 10/40;

Priority Number: 1998-08-18 JP1998000232027

Abstract: PROBLEM TO BE SOLVED: To provide a battery having an excellent cycle characteristic by making a negative electrode mix density appropriate by using a molded product comprising a mixture containing a predetermined compound lithium-containing nitride, a carbon material and a binder and having a density of a specific range as an active material of a negative electrode.

SOLUTION: A molded product comprising a mixture containing a compound lithium-containing nitride represented by a formula: Li3-x-yMxN (M represents at least one transition element selected from a group consisting of Ti, V, Cr, Fe, Co, Ni and Cu, $0.1 \leq x \leq 0.8$, $0 \leq y \leq 2-x$); a carbon material; and a binder is used as an active material of a negative electrode for a lithium secondary battery. Then, the density of the molded product is 1.0 g/cm³ or more to 1.95 g/cm³ or less, preferably 1.4 g/cm³ or more since a contacting state between active material particles and between the active material particle and a conductive material particle inside a mix is varied depending on a mix density and an electrode characteristic is largely



View Image


1 page

influenced by the mix density of a plate.
COPYRIGHT: (C)2000,JPO

Family: None


Forward
References:

Go to Result Set: Forward references (1)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US6706447	2004-03-16	Gao; Yuan	FMC Corporation, Lithium Division	<u>Lithium metal dispersion in secondary battery anodes</u>

Other Abstract
Info:

CHEMABS 132(13)168761S CHEMABS 132(13)168761S DERABS C2000-262673 DERABS C2000-262673



[Nominate this for the Gallery...](#)

THOMSON

Copyright © 1997-2006 The Thomson Corporation

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)